

Reference #: 15-003
Date: 12th October 2015

DA Series Building Occupant Warning Modules - Upgrade

NOTIFIER is pleased to announce the release of the Version 4.01 Build 06 firmware for the DA Series Building Occupant Warning Modules (BOWS).

The DA series BOWS amplifier and accessories provides a comprehensive and feature packed solution to building occupant warning systems consisting of digital tone generation and integrated speech messages.

This upgrade includes the following changes:

- When the network is set for New Zealand, the S/C fault will not be added when the amplifier is in alert or evacuation or PTT. A 40 seconds delay has been added for detecting of this fault when the amplifier is exiting alert, evacuation or PTT.
- The sound level of the recorded voice messages have been changed to match the level of the tones. This improves the intelligibility of the voice message considerably.
- New options have been added to the Chime and Lockdown buttons. Each of the two buttons can now be selected to play the messages 1 to 12, or to play the tone/message cycle of evacuation and alert.
- The alert and evacuation output to the strobe card has added options that can be activated when the OWS is in
 - Alert,
 - Evacuation,
 - Amplifier active or
 - Paging (PTT) active.

Note:

- This software is only integrated in new systems.
- The system version of the module can be found in the *Diagnostics Menu*. (Refer to manual section 7.3 *Accessing Firmware Revisions*.)

Part #	Description
ASY-02-002	DA 30 - 30 Watt building occupant warning system
ASY-02-003	DA 60 - 60 Watt building occupant warning system
ASY-02-004	DA 120 – 120 Watt building occupant warning system

For any additional information please contact your NOTIFIER Systems Consultant, your regional NOTIFIER office or visit www.notifier.com.au.